



BROOKFIELD VISCOMETER DIGITAL DV-E

DESCRIPTION

Digital entry-level instrument for the viscosity measuring directly on display. The viscometer DV-E with LCD display is the low-cost instrument off the range and natural tech-evolution of the analogical version. Full compatibility with all accessories from the Brookfield range. The LCD display simultaneously shows: the viscosity in cP or mP·s, torque %, rpm speed and number of spindle installed, auto-determination of viscosity scale.

TECHNICAL SPECIFICATIONS

- Accuracy: $\pm 1\%$ of range
- Repeatability: $\pm 0,2\%$
- 18 speeds for a complete choice range
- Supply: 230 V - 50 hz single phase

EQUIPMENT

- Hard plastic carrying case
- Stand and guard leg
- Appropriate spindle set

ACCESSORIES AND SPARE PARTS

GT0908	Water baths digital up to 200 °C
GT0909	Thermosel heaters up to 300 °C
GT0910	Helipath stand with 6 T-bar spindle
GT0911	Spiral adapter includes two spiral spindles
GT0912	Small sample adapter with spindle and chamber
GT0913	UL adapter with spindle and chamber
GT0914	DIN adapter with 3 spindles
GT0915	Standard spindles set AISI-302 for LV/RV/HA/HB
GT0916	6 T-bar spindles set with adapter
GT0917	Viscosity standard liquid for calibration control

CODE	MODEL	VISCOSITY RANGE	RPM	SPEED N°	SPINDLE N°	OVERALL DIMENSION	WEIGHT
GT0941	LVDV-E	1÷2.000.000	0,3 ÷ 100	18	4	450x350x200 mm	9 kg
GT0942	RVDV-E	100 ÷ 13.000.000	0,3 ÷ 100	18	6	450x350x200 mm	9 kg
GT0943	HADV-E	200 ÷ 26.000.000	0,3 ÷ 100	18	6	450x350x200 mm	9 kg
GT0944	HBDV-E	800 ÷ 104.000.000	0,3 ÷ 100	18	6	450x350x200 mm	9 kg