



BROOKFIELD VISCOSIMETER DIGITAL DVNEXT

DESCRIPTION

7" Touch Screen instrument for the measuring of viscosity with all data reading on display, serial output RS-232 C to connect a PC PG FLASH software. Full interchangeable to Brookfield accessories range. The display shows simultaneously: viscosity in °cP or °F, shear rate, shear stress

TECHNICAL SPECIFICATIONS

- Accuracy: ± 1% of range
- Repeatability: ± 0,2 %
- 2600 speeds for a complete choice range
- Analogical output 0-1 Vdc and RS-232C
- Programs features: 4 customize prog., time to torque / stop
- Supply: 230 V-50 hz single phase

EQUIPMENT

- Hard plastic carrying case.
- Stand and guard leg
- Appropriate spindle set
- Temperature probe for monitoring samples
- PG Flash software

ACCESSORIES AND SPARE PARTS

GT0908	Water baths digital up to 200 °C
GT0909	Thermosel heaters up to 300 °C
GT0910	Helipath stand with 6 T-bar spindle
GT0911	Spiral adapter includes two spiral spindles
GT0912	Small sample adapter with spindle and chamber
GT0913	UL adapter with spindle and chamber
GT0914	DIN adapter with 3 spindles
GT0915	Standard spindles set AISI - 302 for LV/RV/HA/HB
GT0916	6 T - bar spindles set with adapter
GT0917	Viscosity standard liquid for calibration control
GT0936	Rheocalc software

CODE	MODELLO	VISCOSITY RANGE	RPM	SPEEDS N°	SPINDLES N°	OVERALL DIMENSIONS	WEIGHT
GT0937	DVNXLV	1 ÷ 6.000.000	0,1 ÷ 200	2600	4	450x350x200 mm	9 kg
GT0938	DVNXRV	100 ÷ 40.000.000	0,1 ÷ 200	2600	6	450x350x200 mm	9 kg
GT0939	DVNXHA	200 ÷ 80.000.000	0,1 ÷ 200	2600	6	450x350x200 mm	9 kg
GT0940	DVNXHB	800 ÷ 320.000.000	0,1 ÷ 200	2600	6	450x350x200 mm	9 kg