



## ELECTRONIC BALANCES

### DESCRIPTION

Precision electronic balances single range with milligram, centigram, decigram resolutions.

### TECHNICAL SPECIFICATIONS

- Digital display with integrated key
- Measuring units selection: g, ct, oz, lb, dwt, GN, tl, momme
- Filter for vibrations damping selection
- Automatic calibration by means of reference weight
- Tare from 0 (zero) g up to full capacity
- Serial output RS232-C
- Operating temperature: 10 ÷ 30 °C
- Supply: 230 V - 50/60 Hz single phase

### ACCESSORIES AND SPARE

<b>GT0412</b>	External printer RS232-C for balance
<b>GT0705</b>	Connection cable RS232-C balance - PC
<b>GT0706</b>	Connection cable RS232-C balance - printer

CODE	MODEL	CAPACITY	PAN SIZE	READABILITY	LINEARITY	CALIBRAT. WEIGHT	DIMENSION	WEIGHT
<b>GT0711</b>	520	520 g	Ø 110 mm	0,001 g	± 0,002 g	Internal 200 g	194x325x315 mm	9 kg
<b>GT0713</b>	1000	1000 g	Ø 160 mm	0,01 g	± 0,01 g	External 200 g	194x325x315 mm	9 kg
<b>GT0715</b>	2200	2200 g	Ø 160 mm	0,01 g	± 0,02 g	External 1 kg	194x325x315 mm	5,5 kg
<b>GT0718</b>	4100	4100 g	Ø 160 mm	0,01 g	± 0,02 g	External 2 kg	194x325x315 mm	6,5 kg
<b>GT1380</b>	5200	5200 g	Ø 160 mm	0,01 g	± 0,1 g	External 2 kg	194x325x165 mm	6,5 kg
<b>GT1381</b>	6200	6200 g	Ø 160 mm	0,01 g	± 0,1 g	External 2 kg	194x325x165 mm	6,5 kg
<b>GT0722</b>	10000 RP	10000 g	195x175 mm	0,1 g	± 0,1 g	External 2 kg	200x325x165 mm	6,5 kg
<b>GT1382</b>	25000 RP	25000 g	195x175 mm	0,1 g	± 0,1 g	External 2 kg	200x325x165 mm	6,5 kg
<b>GT0721</b>	4500 RP	4500 g	195x175 mm	0,1 g	± 0,1 g	External 2 kg	200x325x165 mm	6,5 kg
<b>GT0723</b>	6500 RP	6500 g	195x175 mm	0,1 g	± 0,1 g	External 2 kg	200x325x165 mm	6,5 kg